

No.	Clasif.	Descripción	No.	Clas.	Description
1	Rv-402	Cuerpo Mezclador Monomando Reg.	1	Rv-402	Regular Single Dispensing Mixer Body
2	Rv-740	O´Ring 2-028	2	Rv-740	2-028 O´ring
3	Rv-401	Porta Cartucho Monom. Reg.	3	Rv-401	Shower Single Control Cartridge Holder
4	Sh-370	Cartucho Armado Gmd Lavabo	4	Sh-370	Assembled Lavatory Cartridge
5	Rh-613	Tuerca 1-1/2" 24 Uns-2A	5	Rh-613	1-1/2 24 Uns 2A Nut
6	Rh-724	Chapetón Monomando Sable	6	Rh-724	Sable Single Control Plate
7	Sv-076	Chapetón Con Sello Monomando Axiss	7	Sv-076	Axiss Single Control Plate With Seal
8	Rv-411	Tornillo 10-24 Unc - 2A X 1 3/4"	8	Rv-411	10-24 Unc - 2A X 1 3/4" Screw
9	Sv-071	Cubre Tornillos Con Sello	9	Sv-071	Screw Cover With Seal
10	Rh-746	Maneral Monomando Sable	10	Rh-746	Sable Single Control Faucet Handle
11	Ra-400	Opresor No.8 23/64	11	Ra-400	No. 8 23/64 Setscrew
12	Rh-085	Tapón Macho Cuerpo Duplex	12	Rh-085	Duplex Body Male Cap

Sub-ensambles

13 Sh-417 Maneral Sable

Sub-assemblies

13 Sh-417 Sable Faucet Handle

Características:
Cartucho Monomando
Cerámico

Features:
Ceramic Cartridge

Datos Técnicos:
Material:
Latón

Technical Information:
Materials:
Brass

Conexión:
1/2" - 14 Npt

Inlet Thread:
1/2" - 14 Npt

Presión de Trabajo:
Pmin = 0.8 Kg/Cm2
[11.4 Psi]
Pmax = 6.0 Kg/Cm2
[85.34 Psi]

Working Pressure:
Pmin = 0.8 Kg/Cm2
[11.4 Psi]
Pmax = 6.00 Kg/Cm2
[85.34 Psi]

Ajuste de
Instalación:
25.4 Mm [1"] Max.

Shower Valve Installation
Depth Range:
25.4 Mm [1"] Max

Precaución:
No Retirar la Cubierta
Hasta Haber Colocado El
Acabado Final Del Muro

Caution:
Do Not Remove Before
Setting The Final Finish
On The Wall

